

# AOSHENG®

CREATES A GREEN WORLD



## Product Catalogue



科技营造绿色世界

动力世家 匠心传承


NINGBO·CHINA  
[www.aosheng.com.cn](http://www.aosheng.com.cn)

# Technology creates a green world



A Factory

## Company Introduction & Innovation History



# AOSHENG



B Factory

equipment  
capacity

The second factory(7000m<sup>2</sup>) was founded and began to use. We research Petrol Water Pump, Blower and Hedge Trimmer.

Aosheng started to research the top-end series 4stroke Hybrid engine which can run 300hours and Pass EPA Euro-V

0

2012

2016

2018

2019

Aosheng started to launch into domestic market And developed fast

Company created new brand –HENX For 36V 48V battery Garden machine series


Occupies 10000 square meters factory area ,has more than 500 employees. There are have 9 main series products, ,more then 60models.Sale to all of the world

## PRODCUTS R&D

AOSHENG R&D led by Japanese engineer who used in MITSUBUSHI HEAVY INDUSTRIES more than 20 years .His team consists of 40 skilled technicians. the products R&D center and lab which equipped with the advanced testing device, such as dynamometer machine, exhaust emission machine, fans testing machine, three-dimensional measuring machine, material testing machine, spectrum analyzer ect. We have advanced design concept and the key technology that meet engine emission requirements. A variety of our engines have passed the Euro V and EPA attestation.AOSHENG efforts to be a first-class manufacturer like STIHL MAKITA MITSUBUSHI ect




# AOSHENG



# Workshop

# AOSHENG



## Quality management& Exhaust Technology



## Quality management& Exhaust Technology

Aosheng has the domestic first-class products testing center .All accessories process and products Are tested by Aosheng own test programs .These tests and inspections are up to ISO9001 standard.



## Clean Exhasut Technology

Aosheng engineers have patent technology to reduce the unburned emission of engine so that can comply with even the most strict emission standard like EPA EURO-V

# PRODUCTS DISPLAY





# PRODUCTS CERTIFICATIONS

As one of biggest manufacturers in Agricultral and Garden machinery in China, we always develop and produce the energy conervation. Environmental protection, high-quality and high-efficient products. Our company took the lead in passing the evaluation of ISO9001 and ISO14001 Quality Management System. Insistant technological innovation and constant quality control make our products pass GS, CE, EPA and Euro-V certificates.

		<b>UNITED STATES ENVIRONMENTAL PROTECTION AGENCY</b> <b>2017 MODEL YEAR</b> <b>CERTIFICATE OF CONFORMITY</b> <b>WITH THE CLEAN AIR ACT</b>		<b>OFFICE OF TRANSPORTATION</b> <b>AND AIR QUALITY</b> <b>ANN ARBOR, MICHIGAN 48105</b>	
<b>Certificate Issued To:</b> Ningbo AOSHENG Machine Co.,Ltd (U.S. Manufacturer or Importer) <b>Certificate Number:</b> HSHSS.0494GD-065		<b>Effective Date:</b> 11/10/2016 <b>Expiration Date:</b> 12/31/2017		 <b>Byron J. Bunker, Division Director</b> Compliance Division	
<b>Manufacturer:</b> Ningbo AOSHENG Machine Co.,Ltd <b>Engine Family:</b> HSHSS.0494GD <b>Useful Life:</b> 50 Hours / 5 Years <b>Engine Class:</b> Handheld-Class IV <b>Fuel:</b> Gasoline (up to and including 10% Ethanol) <b>Emission Standards:</b> HC + NOx (g/kWh-hr): 50 CO (g/kWh-hr): 305					
Pursuant to Section 213 of the Clean Air Act (42 U.S.C. section 7547), 40 CFR Part 1054, 40 CFR Part 1068 and 40 CFR Part 60 (stationary only and combined stationary and mobile), and subject to the terms and conditions prescribed in those provisions, this certificate of conformity is hereby issued for the following small nonroad engine family, more fully described in the documentation required by 40 CFR Part 1054 and produced in the stated model year. This certificate of conformity covers only those new small nonroad engines which conform in all material respects to the design specifications that applied to those engines described in the documentation required by 40 CFR Part 1054 and which are produced during the model year stated on this certificate of the said manufacturer, as defined in 40 CFR Part 1054. This certificate of conformity does not cover small nonroad engines imported prior to the effective date of the certificate. It is a term of this certificate that the manufacturer shall consent to all inspections described in 40 CFR 1068.20 and 1068. Subpart F and authorized in a warrant or court order. Failure to comply with the requirements of such a warrant or court order may lead to revocation or suspension of this certificate for reasons specified in 40 CFR Part 1054. It is also a term of this certificate that this certificate may be revoked or suspended or rendered void <i>ab initio</i> for other reasons specified in 40 CFR Part 1054, 40 CFR Part 1068. This certificate does not cover small nonroad engines sold, offered for sale, or introduced, or delivered for introduction, into commerce in the U.S. prior to the effective date of the certificate.					

	
<b>CERTIFICATE</b> for EC-Type Examination EC Directive 2006/42/EC Article 12, Section 3b Machinery	
<b>Registration No.:</b> BM 50412712 0001 <b>Report No.:</b> 50148937 001	
<b>Holder:</b> Ningbo Aosheng Machine Co.,Ltd No. 77 West Nantang Road, LinShan Industrial Park, Yuyao, Zhejiang 315462 P. R. China	
<b>Product:</b> Garden Tool (Hand function tool, gasoline)	
<b>Identification:</b> Type Designation: D9-2 Serial No: 107 Engine Model: 1.1-010 Cylinder Capacity: 21,0cm³	
This product is in conformity with all requirements of Annex I of Council Directive 2006/42/EC. This EC-Type Examination Certificate refers to an evaluation of the above mentioned product as stipulated in Annex IX and documented in the s.m. Technical Report. It does not imply an assessment of the whole production and does not permit the use of a mark of conformity of TÜV Rheinland. The holder of certificate is authorized to use this EC-Type Examination Certificate in connection with the EC-declaration of conformity according to Annex II of the Directive. <b>Valid till:</b> 28.08.2023 <b>Date:</b> 29.08.2018 TÜV Rheinland LGA Products GmbH - Tillystraße 2 - 90431 Nürnberg Accredited by Zentralrat der Länder für Sachverständigen (ZLS). Notified under No. 0197 to the EC Commission. CE The CE marking may be used if all relevant and effective EC Directives are complied with. CE	

 LE GOUVERNEMENT DU GRAND-DUCHÉ DE LUXEMBOURG Ministère de la Mobilité et des Transports publics Département de la mobilité et des transports	SOCIÉTÉ NATIONALE DE CERTIFICATION ET D'OMOLOGATION S.N.C. Reporte de Conformité: 027/05  L.4201 Sandweiler
<b>RECEPTEUR</b> 013720161628*20161628S1A1P*0454*000 <b>Annexes:</b> Rapport technique Fiche de renseignements du constructeur Luxembourg, le 29 août 2019	
<b>CERTIFICAT DE RECEPTION UE PAR TYPE</b> EU-TYPE-APPROVAL CERTIFICATE	
<b>Communication concernant l'UE / Communication concerning the EU:</b> - la réception UE par type (EU type approval) - l'estimation de la réception UE par type / estimation of EU type approval - la réception UE par type (EU type approval)	
d'un type de moteur / d'une famille de moteurs qui se réfère aux émissions de gaz polluants et de particules polluantes conformément au règlement (UE) 2016/1628, modifié en dernier lieu par le règlement (UE) 2018/1832, (de la Commission) (du Parlement européen et du Conseil) (ci-après "le règlement") (EU engine type approval and particulate emission regulation pursuant to Regulation (EU) 2016/1628, as last amended by (Commission Delegated) Regulation (EU) 2018/1832, of the Council)	
<b>Numéro de réception UE par type:</b> 013720161628*20161628S1A1P*0454*000 <b>Motif de l'examen/la révision relatif:</b> not applicable	
<b>SECTION 1</b> SECTION 1	
1.1. Marque (dénomination) commerciale du constructeur Trade name of manufacturer	AOSHENG
1.2. Appellation commerciale (le cas échéant) Commercial name of applicant	not applicable
1.3. Nom et adresse du constructeur Company name and address of manufacturer	Ningbo AOSHENG Machinery Co., Ltd. Changshang Village, Linshan Town, Yuyao City, Zhejiang Province, P. R. China
1.4. Nom et adresse du représentant agréé du constructeur (UE) à Bucharest Name and address of manufacturer's authorized representative (EU) in Bucharest	RUIRIS IMPCS SRL STR. CALDA SEVERINULUI NR. 10 CRAIOVA, DJUJ, ROMANIA
1.5. Nom(s) et adresse(s) des usines d'assemblage fabrication Name(s) and address(es) of assembly/manufacturing plant(s)	Ningbo AOSHENG Machinery Co., Ltd. Yueqiang Industrial Park, Linshan Town, Yuyao city, Zhejiang Province, P. R. China

 TÜV SÜD Product Service	
<b>CERTIFICATE</b> No. Z1A 16 11 81201 021	
<b>Holder of Certificate:</b> Ningbo Aosheng Machine Co., Ltd. LinShan Industrial Park 315462 Yuyao, Zhejiang PEOPLE'S REPUBLIC OF CHINA	
<b>Factory(ies):</b> 81201	
<b>Certification Mark:</b> 	
<b>Product:</b> Leaf blower	
<b>Model(s):</b> EBV260, EB260	
<b>Parameters:</b> Displacement: 26cm³ Max. engine power: 0.7kW/7000/min Max. engine speed: 7200/min	
<b>Tested according to:</b> EN 15693:2006/A2:2015 APS GS 2014-01 PAK	
The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. See also notes overleaf.	
<b>Test report no.:</b> 7040313101101-02 <b>Valid until:</b> 2021-12-07	
<b>Date:</b> 2016-12-06 Page 1 of 1	
TÜV SÜD Product Service GmbH - Zertifikatsstelle - Rixstraße 65 - 83338 München - Germany	

 TÜV SÜD Product Service	
<b>Attestation of Conformity</b> No. M8A 16 11 81201 020	
<b>Holder of Certificate:</b> Ningbo Aosheng Machine Co., Ltd. LinShan Industrial Park 315462 Yuyao, Zhejiang PEOPLE'S REPUBLIC OF CHINA	
<b>Product:</b> Leaf blower	
<b>Model(s):</b> EBV260, EB260	
<b>Parameters:</b> Displacement: 26cm³ Max. engine power: 0.7kW/7000/min Max. engine speed: 7200/min	
<b>Tested according to:</b> EN 15693:2006/A2:2015	
This Attestation of Conformity is issued on a voluntary basis according to Council Directive 2006/42/EC relating to machinery. It confirms that the listed equipment (not Annex IV equipment) complies with the principal protection requirements of the directive. It refers only to the sample submitted to TÜV SÜD Product Service GmbH for testing and certification. See also notes overleaf.	
<b>Test report no.:</b> 7040313101101-02	
<b>Date:</b> 2016-12-08	
CE After preparation of the necessary technical documentation as well as the EC declaration of conformity the required CE marking can be affixed on the product. Other relevant directives have to be observed.	
Page 1 of 1 TÜV SÜD Product Service GmbH - Zertifikatsstelle - Rixstraße 65 - 83338 München - Germany	



History R&D showroom Certifications	01-09
Brushcutter	11-16
Blower	17-18
Water Pump	19-20
Pole saw / Multi tools	21-22
Sprayer / Drilling machine	23-24
Hedge trimmer / 48V Lithium scisser	25-26
Olive shaker / Lithium oiveshaker	27-28
Blower / Mist duster	29-30
Lawnmower	31-32
Sprayer / Brushcutter	33-34
OPTIONAL PARTS	35-36



**EURO-V**



# AOSHENG /Brushcutter

**PRO**  
Brushcutter

## Auto stop switch

If the machine is turned off, the stop button returns to start position automatically

## Anti-vibration system

The anti-vibration tube reduce vibration .the user will be more comfortable

**CG145/CG151**

## shaft

Strong 28x2mm shaft and 8x9mm drive shaft


new

## Bigger protector

It can offer 165mm cut width . Work efficiency increase so much



# AOSHENG /Brushcutter



SPECIFICATIONS	CG145	CG151
Structure	OHC	OHC
Inner diameter/Stroke	42/32mm	45/32mm
Displacement	44.3cc	50.9cc
Max power	1.52kw/7500rpm	1.70kw/7000rpm
Max Torque	2.25N.m/6000rpm	2.4N.m/5000rpm
Fuel tank	1.29L	1.29L
Weight	5.1kg	5.2kg
Fuel consumption	480g/kw.h	450g/kw.h
HC+NO(EPA&CARB≤72)	15.6	17.6
CO(EPA&CARB≤536)	388	408
Use micture fuel	40:1	40:1



EURO-V



# AOSHENG /Brushcutter

**PRO**  
Brushcutter

new



**BG151/BG145**



## SPECIFICATIONS

	BG145	BG151
Structure	OHC	OHC
Inner diameter/Stroke	42/32mm	45/32mm
Displacement	44.3cc	50.9cc
Max power	1.52kw/7500rpm	1.70kw/7000rpm
Max Torque	2.25N.m/6000rpm	2.4N.m/5000rpm
Fuel tank	1.29L	1.29L
Weight	5.1kg	5.2kg
Fuel consumption	480g/kw.h	450g/kw.h
HC+NO(EPA&CARB≤72)	15.6	17.6
CO(EPA&CARB≤536)	388	408
Mixed fuel ratio	40:1	40:1



EURO-V



# AOSHENG /Brushcutter

**PRO**  
Brushcutter

**CG430GX/CG520GX**



**CG430GX-H/CG520GX-H**



Professional brushcutter and Clearing saws  
Comfortable, durable and powerful professional tools

TECHNICAL SPECIFICATIONS	CG430GX	CG520GX
Displacement	43cc	52cc
Mating Power	1E40F-5GX	1E44F-5GX
Power	1.25/6500kw/r/min	1.46/6500kw/r/min
Carburetor type	Diaphragm	Diaphragm
Mixed Fuel Ratio	40:1	25:1
Work rod diameter	26/28mm	26/28mm
Fuel tank	1.2L	1.2L
Weight	10.3kg	10.3kg



EURO-V



# AOSHENG /Brushcutter

**PRO**  
Brushcutter



**CG330B/430B/520B**



**BG330B/430B/520B**

SPECIFICATIONS	CG330B	CG430B	CG520B	BG330B	BG430B	BG520B
Displacement	33cc	43cc	52cc	33cc	43cc	52cc
Mating Power	1E36F-2B	1E40F-5B	1E44F-5B	1E36F-2B	1E40F-5B	1E44F-5B
Power	0.9kw/8000r/min	1.25/6500kw/r/min	1.46/6500kw/r/min	0.9kw/8000r/min	1.25/6500kw/r/min	1.46/6500kw/r/min
Carburetor type	Diaphragm	Diaphragm	Diaphragm	Diaphragm	Diaphragm	Diaphragm
Mixed Fuel Ratio	40:1	40:1	40:1	40:1	40:1	25:1
Work rod diameter	26/28mm	26/28mm	26/28mm	26mm	28mm	28mm
Weight	8.5kg	8.5kg	8.5kg	10.62kg	10.62kg	10.62kg



**EURO-V**



# AOSHENG /Brushcutter

**4** STROKE Engine

**CG350A-GX**



**BG350A-GX**



Excellent torque for demanding jobs 38cc 4-stroke engine New deflector design for increased operator visibility Excellent balance and feel Ergonomically designed and Easy to start with air purge and Smart Start.

TECHNICAL SPECIFICATIONS	CG350A-GX	BG350A-GX
Displacement	38cc	38cc
Mating Power	140F-GX	140F-GX
Power	0.9/6500kw/r/min	0.9/6500kw/r/min
Carburetor type	Diaphragm	Diaphragm
Mixed Fuel Ratio	Separate	Separate
Work rod diameter	26/28mm	26/28mm
Weight	8.3kg	10kg



**EURO-V**



**CE**

# AOSHENG /Brushcutter

**2** STROKE  
Engine



**CG630**



**BG630**

**Excellent torque for demanding jobs  
63cc 2-stroke engine New deflector  
design for increased operator visibil-  
ity Excellent bal- ance**



## TECHNICAL SPECIFICATIONS

	<b>BG630</b>	<b>CG630</b>
Engine Type	Air Cooling Single Cylinder.2-stroke	Air Cooling Single Cylinder,2-stroke
Mating Power	1E48F	1E48F
Displacement	63cc	63cc
Power	2.4kw/6500rpm	2.4kw/6500rpm
Carburetor type	Diaphragm	Diaphragm
Mixed Fuel Ratio	25:1	25:1
Fuel consumption	640g/km.h	640g/km.h
Fuel tank	1L	1L



**EURO-V**



**CE**

## Power family, craftsmanship inheritance tough and reliable warrior



### TECHNICAL SPECIFICATIONS G45

Powe	1E40F-7	Fuel ratio	25:1
Cylinder size	40mm	Net weight	7.7kg
Displacement	42cc	Fuel consumption rate	≤600g/kw.h
Power	1.54kw/6500rpm/min	Shaft pipe	φ 28mm
Oil tank	800ml	L*W*H	34X34X28(CM)/166X11X11(CM)

## Power family, craftsmanship inheritance

tough and reliable warrior



### TECHNICAL SPECIFICATIONS

### G45B

Powe	1E40F-7	Fuel ratio	25:1
Cylinder size	40mm	Net weight	7.7kg
Displacement	42cc	Fuel consumption rate	≤600g/kw.h
Power	1.54kw/6500rpm/min	Shaft pipe	φ 28mm
Oil tank	800ml	L*W*H	34X34X28(CM)/166X11X11(CM)

# AOSHENG /Multi tools

**PRO**  
Multi tools



SPECIFICATIONS	DG260	DG430	DG520
Displacement	26cc	43cc	52cc
Mating Power	1E34F-5B	1E40F-5B	1E44F-5B
Power	0.7/6500kw/r/min	1.25/6500kw/r/min	1.46/6500kw/r/min
Carburetor type	Diaphragm	Diaphragm	Diaphragm
Mixed Fuel Ratio	40:1	40:1	25:1
Work rod diameter	26mm	26mm	26mm
Hedge trimmer blade	40cm	40cm	40cm
Bar size	12inch	12inch	12inch

EURO-V   CE



Automotive grade air filter system



ergonomic straps

# E (EB1800D) Electric start

**1800m<sup>3</sup>/H** AIR VOLUME

**MAX. AIR VELOCITY :90M/S**

Clearing Large Amounts of Leaves.  
Dusting.  
Removing Shallow Snow.



**EB1800D**



Electric start button-button start



**EB1800**

Envelope design without naked parts

Large volume oil tank to guarantee extremely long runtime

Free adjustment of the blowing angle



Metal air outlet (optional)

**PRO**  
Brushcutter

## TECHNICAL SPECIFICATIONS

	EB1800	EB1800D
Displacement	75.6cc	75.6cc
Mating Power	1E51F	1E51F
	3.0/7200kw/r/min	3.0/7200kw/r/min
Mixed Fuel Ratio	25:1	25:1
Fuel consumption	544g/kw.h	544g/kw.h
Fuel Capacity	3L	3L
Air volume	0.5m <sup>3</sup> /s	0.5m <sup>3</sup> /s
	12.6kg	12.6kg

## EBV260/EB260



## EB310



The AOSHEG handheld gas leaf blower offers the convenience and power you desire. The 26cc, 2-cycle gas engine is lightweight and powerful with high performance air volume and air speed up to

TECHNICAL SPECIFICATIONS	EB260/EBV260	EB310
Displacement	26cc	31cc
Mating Power	1E34FC	1E37F
Power	0.7/7000kw/r/min	1.0/6500kw/r/min
Mixed Fuel Ratio	40:1	40:1
Carburetor type	Diaphragm	Diaphragm
Air volume	0.19m³/s	0.23m³/s
Weight	5.56kg	6.56kg

# AOSHENG / WATER PUMP

**4** STROKE Engine



**QGZ25/40-30C**



**SPECIFICATIONS**

	<b>QGZ25-30C/QGZ40-30C</b>	<b>QGZ25-30C/QGZ40-30C</b>
Displacement	38cc	38cc
Mating Power	140F	140F
Power	0.9/6500kw/r/min	0.9/6500kw/r/min
Mixed Fuel Ratio	Separate	Separate
Fuel Capacity	1L	1L
Lift	30m	30m
Outlet diameter	1" /1.5"	1" /1.5"
Weight	7.48kg	7.48kg



**QGZ25/40-30-GX**



## QGZ25/40-30-5B



## QGZ40-30-5BA



## QGZ25/40-30

Our Water Transfer Pump is designed for handle the Toughest Jobs. Use to drain a pool in no time, empty a flooded basement, pump out a flooded trench, fill or empty a water storage tank or reservoir, irrigate a field, hose down a construction site and more.

SPECIFICATIONS	QGZ40-30-5BA	QGZ25-30-5B/QGZ40-30-5B	QGZ25-30/QGZ40-30
Displacement	43cc	43cc	40.2cc
Mating Power	1E40F-5	1E40F-5	1E40F-6
Power	1.25/6500kw/r/min	1.25/6500kw/r/min	1.45/7000kw/r/min
Mixed Fuel Ratio	40:1	40:1	40:1
Fuel Capacity	0.85L	0.85L	0.85L
Lift	35m	30m	30m
Outlet diameter	1.5"	1" /1.5"	1" /1.5"
Weight	7.48kg	7.48kg	6.5kg

# AOSHENG / HEDGE TRIMMER

**PRO**  
Brushcutter

**KD260**



This hedge trimmer with safty device when the user fold the blade even the engine still run the blade will stop



## TECHNICAL SPECIFICATIONS


## KD260

Displacement	26cc
Mating Power	1E34F-5B
Power	0.7/7500kw/r/min
Mixed Fuel Ratio	40: 1
Carburetor type	Diaphragm
Work rod diameter	26mm
Weight	5.5kg

EURO-V   CE

# AOSHENG /Dual-edge hedge trimmer

dual-blade easy operation  
fast and effective trim



advanced engine  
with strong power  
and little vibration



Close-mesh  
precision gearbox



## TECHNICAL SPECIFICATIONS

### 3CX-600S/3CX-600H

Power	1E32FL	Cutting width	600mm
Cylinder diameter	32mm	Oil tank volume	550ml
Displacement	22.5cc	Fuel ratio	25:1
Power	0.65kw/7500rpm/min	Net weight	5.5kg
Fuel consumption rate	≤600g	L*W*H	112X25X28(CM)

EURO-V   CE

# AOSHENG /POLE SAW



## AS-GZ330/AS-GZ260



### TECHNICAL SPECIFICATIONS

	AS-GZ330	AS-GZ260
Displacement	33cc	26cc
Mating Power	1E36F-5B	1E34F-5B
Power	0.9/6500kw/r/min	0.7/6500kw/r/min
Mixed Fuel Ratio	40:1	40:1
Carburetor type	Diaphragm	Diaphragm
Length	2-4M	2-4M
Guide Bar Size	12"	12"
Workrod diameter	Φ26mm	Φ26mm

EURO-V   

# AOSHENG /OLIVE SHAKER



**PRO**  
*Olive shaker*



## SPECIFICATIONS

## AS01ZG

Displacement	53.2cc
Mating Power	Kawasaki
Power	2.0/7500kw/r/min
Mixed Fuel Ratio	25:1
Fuel Capacity	1.1L
Length	3-4.5m
Hook the diameter	40mm
Weight	18kg

EURO-V   CE

**AS01ZG**

# AOSHENG /CHAINSAW

High quality filter: reduce dust and noise. Paper filter , good effective to clean air .Easy to maintain.



Safety throttle switch:high quality rubber-cover handle,make user ore comfortable.




Thick u-shaped handle:ergonanic, durable shock absorption.



## AS4500A/AS5200A/AS5800A

Model	AS4500A	AS5200A	AS5800A
Displacement	45cc	49.3cc	55cc
Mating Power	1E43F	1E45F	1E45F
Power	1.8kw/7500r/min	2.0kw/7500r/min	2.2kw/7500r/min
Carburetor type	Butterfly	Butterfly	Butterfly
Idle	3000r/min	3000r/min	3000r/min
Sprocket wheel	7TX 0.325"	7TX 0.325"	7TX 0.325"
Pitch	0.050"	0.058"	0.058"
Chain wide	0.325"	0.325"	0.325"
Fuel consumption	≤610g/kw.h	≤610g/kw.h	≤610g/kw.h
The meadum operating speed	11500rpm	11500rpm	11500rpm
Maximum cutting length	460mm	490mm	550mm
Size guides	18"	20"	22"
Bore X Stroke	Φ43 X31	Φ45X31	Φ45.2 X 34
Fuel capacity	0.47L	0.47L	0.47L
Chain fuel tank capacity	0.23L	0.23L	0.23L
Weight	6.5kg	6.94kg	8.2kg



# AOSHENG /CHAINSAW

**PRO**  
Chainsaw



**AS6880**



**AS3800A**

## TECHNICAL SPECIFICATIONS

	<b>AS600A</b>	<b>AS3800A</b>
Engine Type	Air Cooling Single Cylinder,2-stroke	Air Cooling Single Cylinder,2-stroke
Engine Model	1E46F	1E38F
Max Power	2.8KW/8500r/min	1.25KW/8500r/min
Displacement	60.0cc	38.0cc
Guide Bar Size	18"/20"/22"	12"/16"/18"
IDle Speed	2800-3200r/min	2800-3200r/min
Two-cycle oil/gasoline mixing ratio	1:25	1:25
FuelTank Capacity	550ml	310ml
G.W/N.W	7.1/58kg	6.5/5.1kg

# AOSHENG /MINI TILLER



EURO-V



## TECHNICAL SPECIFICATIONS

	3WG-52	3WG-145
Displacement	52cc	45cc
Mating Power	IE44F-5	AS145
Power	1.46/6500kw/r/min	1.52/7500kw/r/min
Carburetor type	Diaphragm	Diaphragm
Mixed Fuel Ratio	25:1	40:1
Working width	26/28mm	26/28mm
Weight	13kg	14kg


## AS20




## AS20F



# AOSHENG / DRILLING MACHINE



**AS52/43**



earth auger helps with simplifying outdoor work load. It is perfect for digging holes for fence posts and plants and digs through even the toughest soil.

SPECIFICATIONS	AS52	AS43
Displacement	52cc	43cc
Mating Power	1E44F-5	1E40F-5B
Power	1.46/6500kw/r/min	1.25/6500kw/r/min
Mixed Fuel Ratio	25:1	25:1
Drill diameter	Φ200mm	Φ200mm
Reduction	40:1	40:1

EURO-V   CE

# AOSHENG /MIST DUSTER



Control Handle



Booster Pump

**3WF-3GX**



Starter



**3WF-3A-TU**




## TECHNICAL SPECIFICATIONS

	3WF-3GX	3WF-3A-TU
Displacement	42cc	42cc
Mating Power	1E40F-3Z	1E40F-3Z
Power	2.13/7500kw/r/min	2.13/7500kw/r/min
Mixed Fuel Ratio	25: 1	25: 1
Carburetor type	Float	Float
Tank capacity	14/16/20/26L	14/16/20/26L
Horizontal range	≥12m	≥12m
The vertical range	≥8m	≥8m

EURO-V   CE

# AOSHENG /MIST DUSTER



Booster Pump



## Model:3WB-750

0.12CBM

- Mating Power:1E40F-5A
- Displacement:43cc
- Power:1.25kw/7000r/min
- Weight:9.86kg
- Carburetor type:Float type
- Mixed Fuel Ratio:25:1
- Tank capacity:14/20L
- Horizontal range:≥12m
- The vertical range:≥8m



Handle




Rope start



## Model:3WF-80

0.15CBM

- Mating Power:1E52F
- Displacement:77cc
- Power:3.6kw/6500r/min
- Weight:11.56kg
- Carburetor type:Diaphragm
- Mixed Fuel Ratio:25:1
- Tank capacity:17L
- Horizontal range:≥17m
- The vertical range:≥11m



Booster Pump



## Model:3WF-750

0.1CBM


- Mating Power:1E46F-3
- Displacement:57cc
- Power:2.5kw/7500r/min
- Weight:9.88kg
- Carburetor type:Throttle type
- Mixed Fuel Ratio:25:1
- Tank capacity:14/20L
- Horizontal range:≥12m
- The vertical range:≥8m



## Model:3F-30

0.18CBM

- Mating Power:1E46F
- Displacement:58cc
- Power:2.0kw/7500r/min
- Weight:11.32kg
- Carburetor type:Float type
- Mixed Fuel Ratio:25:1
- Tank capacity:30L
- Horizontal range:≥12m
- Tank capacity:30L



Booster Pump



## Model:3WF-3/A/B/C

0.18CBM

- Mating Power:1E40F-3Z
- Displacement:42cc
- Power:2.13kw/7500r/min
- Weight:11.12kg
- Carburetor type:Float type
- Mixed Fuel Ratio:25:1
- Tank capacity:14/16/20/26L
- Horizontal range:≥12m
- The vertical range:≥8m



## Model:3WF-140

0.18CBM

- Mating Power:140F
- Displacement:38cc
- Power:0.9kw/6500r/min
- Weight:13.3kg
- Carburetor type:Diaphragm
- Mixed Fuel Ratio:Separate
- Tank capacity:14/16/20/26L
- Horizontal range:≥12m
- The vertical range:≥8m

# AOSHENG /LAWNMOWER



## Model:AS506SA

0.23CBM


- Mating Power:AS1P70FA
- Displacement:173cc
- Power:3.0kw/3000r/min
- Cutting width:500mm
- Fuel consumption:≤395g/kw.h
- Fuel capacity:1.8L
- Catcher Volum:50-60L
- Mowing heighth:25-80



## Model:AS505HA-C

0.23CBM

- Mating Power:AS1P65FA
- Displacement:139cc
- Power:2.8kw/3000r/min
- Cutting width:500mm
- Fuel consumption:≤420g/kw.h
- Fuel capacity:1.6L
- Catcher Volum:50-60L
- Mowing heighth:25-80



# AOSHENG /LAWNMOWER



**Model:AS506HA-C**

0.23CBM

- Mating Power:AS1P70FA
- Displacement:173cc
- Power:3.0kw/3000r/min
- Cutting width:500mm
- Fuel consumption:≤395g/kw.h
- Fuel capacity:1.8L
- Catcher Volum:50-60L
- Mowing heighth:25-80



**Model:AS506HA**

0.23CBM

- Mating Power:AS1P70FA
- Displacement:173cc
- Power:3.0kw/3000r/min
- Cutting width:500mm
- Fuel consumption:≤395g/kw.h
- Fuel capacity:1.8L
- Catcher Volum:50-60L
- Mowing heighth:25-80



**Model:AS506HC**

0.23CBM

- Mating Power:GXV160
- Displacement:163cc
- Power:2.0kw/3000r/min
- Cutting width:500mm
- Fuel consumption:≤395g/kw.h
- Fuel capacity:1.8L
- Catcher Volum:50-60L
- Mowing heighth:25-80



# AOSHENG /SPRAYER



**Model:AS800D**

0.12CBM

- Mating Power:140F
- Displacement:38cc
- Power:0.9kw/6500r/min
- Weight:10.06kg
- Range:≥9m
- Mixed Fuel Ratio:Separate
- Tank capacity:25L
- Working pressure:1.5-2Mpa
- Plunger diameter:18mm

**4** STROKE Engine



**Model:AS800C**

0.12CBM

- Mating Power:140F
- Displacement:38cc
- Power:0.9kw/6500r/min
- Weight:10.06kg
- Range:≥9m
- Mixed Fuel Ratio:Separate
- Tank capacity:25L
- Working pressure:1.5-2Mpa
- Plunger diameter:18mm



**Model:AS800W**

0.12CBM

- Mating Power:140F
- Displacement:38cc
- Power:0.9kw/6500r/min
- Weight:10.06kg
- Range:≥9m
- Mixed Fuel Ratio:Separate
- Tank capacity:25L
- Working pressure:1.5-2Mpa
- Plunger diameter:18mm

**4** STROKE Engine



**Model:AS800B**

0.12CBM

- Mating Power:140F
- Displacement:38cc
- Power:0.9kw/6500r/min
- Weight:10.06kg
- Range:≥9m
- Mixed Fuel Ratio:Separate
- Tank capacity:25L
- Working pressure:1.5-2Mpa
- Plunger diameter:18mm



**Model:AS768A**

0.11CBM

- Mating Power:1E33F
- Displacement:26cc
- Power:0.65kw/6500r/min
- Weight:8.74kg
- Range:≥9m
- Mixed Fuel Ratio:25:1
- Tank capacity:25L
- Working pressure:1.5-2Mpa
- Plunger diameter:18mm



# AOSHENG / BRUSHCUTTER

**Model:CG260**



0.038CBM

- Mating Power:1E34F-B
- Displacement:26cc
- Horsepower:1HP
- Weight:6kg
- Mixed Fuel Ratio:25:1

**Model:CG330**



0.038CBM

- Mating Power:1E36F-2
- Displacement:33cc
- Horsepower:1.3HP
- Weight:7.8kg
- Mixed Fuel Ratio:25:1

**Model:CG430**



0.038CBM

- Mating Power:1E40F-5
- Displacement:43cc
- Horsepower:1.8HP
- Weight:8kg
- Mixed Fuel Ratio:25:1

**Model:CG520**



0.038CBM

- Mating Power:1E44F-5
- Displacement:52cc
- Horsepower:2HP
- Weight:9.0kg
- Mixed Fuel Ratio:25:1

**Model:CG260T**



0.038CBM

- Mating Power:EB26
- Displacement:26cc
- Horsepower:1HP
- Weight:6kg
- Mixed Fuel Ratio:25:1

**Model:CG330T**



0.038CBM

- Mating Power:TB33
- Displacement:33cc
- Horsepower:1.3HP
- Weight:7.8kg
- Mixed Fuel Ratio:25:1

**Model:CG430T**



0.038CBM

- Mating Power:TB43
- Displacement:43cc
- Horsepower:1.8HP
- Weight:8kg
- Mixed Fuel Ratio:25:1

**Model:CG520T**



0.038CBM

- Mating Power:TB52
- Displacement:52cc
- Horsepower:2HP
- Weight:9kg
- Mixed Fuel Ratio:25:1

**Model:CG411**



0.038CBM

- Mating Power:1E40F-6
- Displacement:41cc
- Horsepower:2HP
- Weight:8kg
- Mixed Fuel Ratio:25:1

**Model:CG411T**



0.038CBM

- Mating Power:1E40F-6T
- Displacement:41cc
- Horsepower:2HP
- Weight:8kg
- Mixed Fuel Ratio:25:1

**Model:BG430A/BG520A**



0.038CBM

- Mating Power:1E40F-5/1E44F-5
- Displacement:43/52cc
- Horsepower:1.8/2HP
- Weight:13kg
- Mixed Fuel Ratio:25:1

**Model:BG328B**



0.038CBM


- Mating Power:1E36F
- Displacement:30.5cc
- Horsepower:0.87HP
- Weight:10.2kg
- Mixed Fuel Ratio:25:1

# OPTIONAL PARTS


Choose the right type of cutting tools for your job.

---





# TECHNOLOGY CREATES GREEN WORLD



LITHIUM CATALOGUE   GASOLINE CATALOGUE

## **AOSHENG**

Ningbo AOSHENG Machine Co.,Ltd

Add: Linshan Industrial Park, Yuyao, Zhejiang  
Tel: 0086-0574-62037807   0086-0574-62037812   Fax: 86-0574-62037800  
Http://www.aosheng.com.cn   E-mail: aosheng@aosheng.com.cn

